



commercial sectional doors



TC300, white, with full-view windows



AlumaView STANDARD, bronze-anodized



SteelForm STANDARD, white, with oval windows

TC SERIES

THERMAL SECTIONAL DOORS

THERMASEAL™

SECTIONAL THERMAL DOORS

STEELFORM™

SECTIONAL RIBBED DOORS

ALUMAVIEW™

SECTIONAL RAIL & STILE DOORS

DESIGNFORM™

SECTIONAL RAISED PANEL DOORS

STYLEFORM™

SECTIONAL RAISED PANEL DOORS

VISIT US AT: WWW.RAYNOR.COM
CALL: 1-800-4-RAYNOR

OVER HALF A CENTURY OF WORKING WITH ARCHITECTS AND SPECIFIERS

Professionals like you have counted on Raynor commercial doors and operators for more than 50 years. We pride ourselves on fast, individualized product information and service, and we can provide product information via fax or next-day delivery. For your convenience, our commercial specifications and drawings can be downloaded from our website and are available on CD-ROM. Raynor Field Representatives are also available to assist with product specifications as well as to provide technical training. Our exclusive, professional network of over 600 dealers and their commitment to customer service has helped make us recognized experts in the industry for over 50 years. Count on your Raynor Dealer for the proper selection and expert installation you deserve.

NEW! Optional white, powder-coated hardware system is available on TC Series, ThermaSeal™, SteelForm™, DesignForm™ and StyleForm™.



TC SERIES

THERMAL SECTIONAL DOORS

With a proven track record for thermal efficiency and extreme durability, Raynor TC Series is simply the best you can specify. With extruded polystyrene insulation thermally bonded between two steel skins, TC320 and TC300 doors have an exceptional R-value of 17.05. And, 2" thick TC200 doors feature a laminated core of CFC-free expanded polystyrene insulation for an R-value of 10.25.

Series MODEL	Max. Opening Width	Max. Opening Height	Construction	Surface Texture	Section Thickness	Exterior/ Interior Steel Thickness	End Stile Steel Thickness	Insulation (R-Value)	Thermal Break	Exterior Colors	Section Warranty
TC320	32'	24'	Steel Sandwich	Smooth	3"	20-Gauge (.035")/ 25-Gauge (.017")	14-Gauge	Extruded Polystyrene (17.05)	Yes	White & 187 ArmorBrite Colors	1-Year (Any Rust) 10-Year (Delamination)
TC300	32'	24'	Steel Sandwich	Stucco	3"	25-Gauge (.017")/ 25-Gauge (.017")	14-Gauge	Extruded Polystyrene (17.05)	Yes	White, Frost White*, Dark Brown*, Sepia*, Beige* & 187 ArmorBrite Colors	1-Year (Any Rust) 10-Year (Delamination)
TC200	18'	14'	Steel Sandwich	Stucco	2"	26-Gauge (.015")/ 26-Gauge (.015")	18-Gauge	Expanded Polystyrene (10.25)	Yes	White, Almond, ClayTone, BronzeTone, Brown*, Sepia*, Frost White*, Beige*, & 187 ArmorBrite Colors	1-Year (Any Rust) 10-Year (Delamination)

WARRANTY TC Series door sections carry an exclusive 10-year delamination warranty (of the steel door skins from the insulation) and a standard 1-year limited warranty against any rust on all other door components. See your local Raynor Dealer for complete details.



THERMASEAL™

SECTIONAL THERMAL DOORS

For maximum thermal protection, choose ThermaSeal™. An exclusive process fills 100% of the door's interior space with energy-saving polyurethane foam insulation to deliver exceptional R-values of 16.4 for the 1-3/4"-thick model and 14.5 for the 1-1/2" door. Additionally, this process provides superior foam density for excellent structural integrity.

Series MODEL	Max. Opening Width	Max. Opening Height	Construction	Surface Texture	Section Thickness	Exterior/ Interior Steel Thickness	End Stile Steel Thickness	Insulation (R-Value)	Thermal Break	Exterior Colors	Section Warranty
ThermaSeal™ STANDARD	28'	20'	Steel Sandwich	Stucco	1 3/4"	25-Gauge 26-Gauge	16-Gauge	Polyurethane (16.4)	Yes	White, Dark Brown*	1-Year (Rust) 10-Year (Delamination)
ThermaSeal™ BASIC	16'	16'	Steel Sandwich	Stucco	1 1/2"	26-Gauge 26-Gauge	16-Gauge	Polyurethane (14.5)	Yes	White	1-Year (Rust) 10-Year (Delamination)

WARRANTY ThermaSeal™ door sections carry a 1-year limited warranty against any rust and a 10-year limited warranty against delamination (of the steel door skins from the insulating foam). Hardware and springs are warranted for 1-year against defects in materials and workmanship. See your local Raynor Dealer for complete details.

*Features the Kynar™ paint process, which provides extended UV protection against fading



STEELFORM™

SECTIONAL RIBBED DOORS



Ideal for situations that demand maximum reliability, SteelForm™ door sections are a full 2" thick and made of hot-dipped galvanized steel for maximum rust resistance. Available in 16-, 20-, and 24-gauge models, SteelForm™ doors offer a wide selection of quality features and options for commercial and industrial applications.

Series MODEL	Max. Opening Width	Max. Opening Height	Construction	Surface Texture	Section Thickness	Exterior Steel Thickness	End/Center Stile Steel Thickness	Optional Insulation (R-Value)	Exterior Colors	Section Warranty
SteelForm™ OPTIMA (S-16)	24'	24'	Steel Pan	Smooth	2" (Flush)	16-Gauge	13-Gauge/16-Gauge	Polystyrene (7.70) Fiberglass (7.57)	White	1-Year (Rust)
SteelForm™ STANDARD (S-20, S-24)	32' 24'	24' 24'	Steel Pan	Smooth	2" (Ribbed)	20-Gauge 24-Gauge	16 or 13-Gauge/16-Gauge	Polystyrene (7.70) Fiberglass (7.57)	White Frost White*, Dark Brown*, Sepia*, Beige*	1-Year (Rust)
SteelForm™	16'	16'	Steel Pan	Smooth	2"	24-Gauge	16-Gauge/	Polystyrene (7.70)	White	1-Year (Rust)

WARRANTY SteelForm™ doors carry a 1-year limited warranty against any rust. See your local Raynor Dealer for complete details.



ALUMAVIEW™

SECTIONAL RAIL & STILE DOORS

AlumaView™ doors have long been the standard fixture for facilities that require dependable, attractive doors that offer maximum visibility. With an anodized-finished extruded aluminum frame, AlumaView™ door sections are a full 1-3/4" or 2" thick. And, for installations that require a custom look, AlumaView™ offers designer options such as powdercoated colored and textured finishes and architectural glass.

Series MODEL	Max. Opening Width	Max. Opening Height	Overall Section Thickness	End Stile Width	Center Stile Width	Colors	Warranty
AlumaView™ OPTIMA (HL)	24'	24'	2"	3 1/4" or 6 1/4"	3 5/8"	Clear-Anodized Finish or 187 ArmorBrite™ Colors	1-Year
AlumaView™ STANDARD (L)	14'	14'	1 3/4"	2 5/8"	7/16"	Clear-Anodized Finish or 187 ArmorBrite™ Colors	1-Year

WARRANTY AlumaView™ doors carry a 1-year limited warranty. See your local Raynor Dealer for complete details.



DESIGNFORM™

SECTIONAL RAISED PANEL DOORS

When your building's façade needs a classic raised panel design, choose from DesignForm™ doors. With style choices, like mixed panel designs and safety features including finger-protection, DesignForm™ doors offer the aesthetic options of a residential door, combined with the strength of a commercial door. DesignForm™ matches Innovations Series™ residential doors.

Series MODEL	Max. Opening Width	Max. Opening Height	Construction	Panel Configuration	Section Thickness	End/Center Stile Steel Thickness	Insulation (R-Value)	Thermal Break	Exterior Colors	Section Warranty
DesignForm™ OPTIMA (Commercial Affina/Centura)	20'	16'	Steel Sandwich	Colonial Ranch Mixed Flush (Woodgrain)	2"	18-Gauge/ 19-Gauge Plates	Polyurethane (18.0)	Yes	White, Almond, ClayTone, GrayTone, Dark Brown*, Hunter Green*	1-Year (Rust)
DesignForm™ STANDARD (Commercial Relante)	20'	16'	Steel Sandwich	Colonial Ranch Flush (Woodgrain)	1 3/8"	18-Gauge/ 19-Gauge Plates	Polyurethane (13.08)	Yes	White, Almond, ClayTone	1-Year (Rust)

WARRANTY DesignForm™ door sections carry a 1-year warranty against rust and a 1-year limited warranty against any defects in materials or workmanship. See your local Raynor Dealer for complete details.

*Features the Kynar™ paint process, which provides extended UV protection against fading



STYLEFORM™

SECTIONAL RAISED PANEL DOORS

When exterior appearance is a primary consideration, select a raised-panel door from the attractive Raynor StyleForm™ series. StyleForm™ doors, equipped with heavy-duty, commercial-grade hardware, offer the perfect combination of beauty and reliability. StyleForm™ matches Traditions Series™ residential doors.

Series MODEL	Max. Opening Width	Max. Opening Height	Construction	Surface Texture	Section Thickness	End/Center Stile Steel Thickness	Insulation (R-Value)	Thermal Break	Exterior Colors	Section Warranty
StyleForm™ OPTIMA (Commercial Decade ShowCase)	18'	14'	Steel Sandwich	Raised-Panel/ Flush (Woodgrain)	2"	18-Gauge/ N/A	Polystyrene (10.25)	Yes	White, Almond, ClayTone,, Dark Brown*,Frost White*, Beige*, Sepia*, BronzeTone	1-Year (Rust) 5-Year (Delamination)
StyleForm™ STANDARD (Commercial Decade II)	18'	14'	Steel Pan (24-Gauge)	Raised-Panel (Woodgrain)	2"	18-Gauge/ 18-Gauge	Polystyrene-Optional (5.0)	No	White, Almond, ClayTone, Dark Brown*, BronzeTone	1-Year (Rust)
StyleForm™ BASIC (Commercial Classic)	14'	14'	Steel Pan	Raised-Panel (Pebblegrain)	2"	18-Gauge/ 18-Gauge	Polystyrene-Optional (5.0)	No	White, Almond, ClayTone, Dark Brown*	1-Year (Rust)

WARRANTY StyleForm™ door sections carry a 1-year limited warranty against any rust and a 5-year limited warranty against delamination of the steel door skins from the insulating foam. See your local Raynor Dealer for complete details.

*Features the Kynar™ paint process, which provides extended UV protection against fading

POWERHOIST™

O P E R A T O R S

Rugged Raynor PowerHoist™ operators are available in a variety of motor, voltage and phase combinations for any commercial or industrial application.

CONTROLHOIST™

O P E R A T O R S

Raynor ControlHoist™ operators with solid state logic board control are available in various motor and voltage combinations to meet many commercial applications.

Raynor also offers a complete line of commercial rolling and fire doors, as well as traffic doors.



Need AIA credits? Raynor provides courses covering a variety of door subjects. Call 1-800-4-RAYNOR for more information.

CALL
1-800-4-RAYNOR

CLICK
www.raynor.com

FAX
1-815-288-7142



P.O. Box 448
1101 East River Road
Dixon, IL 61021



This information was as complete and factual as possible at the time it was printed. We do, however, reserve the right to make changes in product specifications and availability without notice. Features and options may be different in countries other than the United States. Product colors have been reproduced as well as possible with present commercial printing processes. For absolute accuracy in color matching, use actual product samples.