

## 1/2 HP AC CHAIN DRIVE WIFI® GARAGE DOOR OPENER RELIABLE PERFORMANCE



### KEY FEATURES

**STANDARD**  
Lifting Power

**WIFI**  
Built in

MyQ® Technology makes this opener compatible with multiple home automation platforms:



Visit [LiftMaster.com/WorksWithMyQ](http://LiftMaster.com/WorksWithMyQ) for a full list of MyQ partners.\*

## SMART

**BUILT-IN WIFI** FOR THE EASIEST WAY TO CONNECT THE GARAGE.

**MyQ MOBILE APP** LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

## RELIABLE

**1/2 HP AC MOTOR** IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

**CHAIN DRIVE SYSTEM** FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

**WARRANTY** 4-YEAR MOTOR, 1-YEAR PARTS.

## SECURE

**SECURITY+ 2.0®** SENDS A NEW CODE WITH EVERY REMOTE CLICK.

**POSILOCK®** ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

**ALERT-2-CLOSE** SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

**THE PROTECTOR SYSTEM®** INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

### INCLUDED ACCESSORIES:

#### Multi-Function Control Panel®

Includes lockout controls and accessory programmability.



6080979

882 WRGD

#### 3-Button Remote Control

Operates up to 3 openers or MyQ Light Accessories.



2220178

893 RCX

### POWERFULL ADD-ONS:

#### Mini Universal Remote Control

Compact and portable to provide quick, easy garage access.



2220185

374 UT

#### Remote Light Control

Plug in any lamp to this device to control it with a smartphone or garage remote.



2220174

825 LM

#### Remote Light Switch

Replaces an existing wall switch to control home lighting with a smartphone or garage remote.



2220183

823 LM

#### Garage Door and Gate Monitor

Monitors and closes up to 4 garage doors from any room in the house.



2220175

829 LM

## MASTERFUL ENGINEERING.

### MOTOR

- ½ Horsepower AC
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

### POWER

- 120V AC
- 60 Hz Voltage
- 6A Current Rating
- UL® Listed
- 4' Power Cord (3-Prong)

### MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (16:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **AC WiFi® Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)



### DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	124"	136"	160"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

**7"**  
Per second for door to move upward

**7"**  
Per second for door to move downward

## STANDARD SPECS.

## SECURITY

### SECURITY+ 2.0® RADIO CONTROLS

3-Button Remote Control  
**Operating Range: ~200'**

Operating Temperature: -30°F to 150°F  
Frequency:

- Remote Control: 310, 315 and 390 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Security+ 2.0 Anti-Burglary Coding

### SECURITY+ 2.0 ENCRYPTED CONTROLS

- Multi-Function Control Panel®
- Program Remote Controls
  - Maintenance Alert System
  - Easy WiFi® Setup

## SMART

### MyQ® RADIO

**902-928 MHz**  
50-Channel FHSS  
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

### HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER\*)

\*May require an external adapter depending on the model and year of your vehicle. Visit [HomeLink.com](http://HomeLink.com) for additional information.

## ELECTRICAL

### LIGHTING




- Max. 1 100-Watt Lightbulb
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

## SHIPPING.

**SHIPPING WEIGHT** (in lbs.)

### CARTONS (2)

- CARTON 1: 20" x 12" x 10"  
- Multi-Function Control Panel  
- 3-Button Remote Control  
- Garage Door Opener Head  
- The Protector System® Safety Reversing Sensors
- CARTON 2: 10'4" x 5" x 5" (for 7' Rail)  
- Assembled Solid-Steel Chain T-Rail



## CONVENIENCE AND SAFETY.

- Alert-2-Close with Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights on
- Maintenance Alert System
- Garage Door Opener Capacity of up to 12 Remote Controls, 1 Keyless Entry System and 16 MyQ Devices



†Note: to reduce the risk of injury to persons- ONLY enable Timer-to-Close and MyQ remote operation features when opener is installed on a sectional door.