# Airman® II with WiFi®

1/2 HP AC BELT DRIVE WIFI OPENER WITH INTEGRATED BLUETOOTH TECHNOLOGY



81550RGD
DEPENDABLE PERFORMANCE

### IN THE BOX

# **POPULAR FEATURES**

1/2 HP AC MOTOR is purposefully designed and built to last

**BELT DRIVE SYSTEM** for quiet, maintenance-free performance

**BUILT-IN WIFI** for the easiest way to connect the garage

**MYQ CONNECTED** control, secure and monitor the garage from the myQ app anytime, from anywhere

SECURITY+ 2.0® sends a new code with every remote click

POSILOCK® electronically protects against forced openings

THE PROTECTOR SYSTEM® invisible light beam autoreverses the door if there is an obstruction

INTEGRATED BLUETOOTH TECHNOLOGY Reduces setup time and makes it even easier to connect to the myQ app, other myQ devices and smart home technology solutions.



# MULTI-FUNCTION CONTROL PANEL

Operates the garage door opener and lights from inside the garage.

882RGDW • 6081094



#### 3-BUTTON REMOTE CONTROL

Operate up to 3 openers or MyQ light accessories from one remote

893RGX • 2220188

# **POWERFUL ADD-ONS**



### MYQ SMART CAMERA

Enable secure video capabilities in your garage

SGC1WLM • 6081054



# MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access

374UT • 2220193







#### **MOTOR**

½ horsepower, 1,625 RPM, automatic thermal protection, permanent **lubrication** 

#### **MECHANICS**

- Steel chassis, T-rail and Trolley, full reinforced belt drive mechanism (63:1 gear reduction and adjustable door arm)
- Auto-force adjustment for changing weather and environmental conditions
- · Electronic limits for easy setup
- · AC WiFi logic board with built-in surge suppressor

#### **POWER**

120V AC, 60 Hz voltage, 6A current rating, UL listed, 4' power cord (3-prong)

#### **SPEED**

7" per second upward, 7" per second downward

#### LIGHTING

Max. 100 watt light bulb, enhanced CFL (Compact Florescent) compatible, max. 26 watts

#### **DIMENSIONS**

Opener Head: 15" L x 10" W x 5.75" H

Note: when both decorative doors are open, the width of the opener is 30".

Rail Options:	7'	8'	10'
Installed Length	124"	136"	160"
Max Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"



#### **WARRANTIES**

4 Year: Motor

1 Year: Parts



#### SECURITY+ 2.0®

Radio Controls:

- Operating range ~200'
- Operating temperature: -30°F to 150°F
- 3-button remote control with Security+ 2.0 code format
- Garage door opener with Security+ 2.0 code format
- · Anti-burglary coding

#### **Encrypted Controls:**

- Multi-Function Control Panel®
- · Program Remote Controls
- Maintenance Alert System
- · Easy WiFi Setup

#### **MYQ RADIO**

- 902-928 MHz 50-channel FHSS (frequently hopping spread spectrum)
- Provides 2-way communication from garage door opener and myQ accessories
- Enables monitoring and control of garage door openers via smartphone or tablet

#### HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER)

May require an external adapter depending on the model and year of vehicle. Visit HomeLink.com for additional information.



#### **SHIPPING**

Carton 1 Shipping Details

Dimensions: 20" x 12" x 10" Weight: 20 lbs Contents:

- Garage Door Opener Head
- Multi-Function Control Panel
- 3-Button Remote Control
- The Protector System® Safety Reversing Sensors

Carton 2 Shipping Details

Dimensions: 10'4" x 5" x 5" (for 7' Rail)

Weight: 17 lbs

Contents:

· Assembled Solid-Steel Belt T-Rail

t: To reduce the risk of injury to persons, only enable Timer-to-Close and myO remote operation features when opener is installed on a sectional doo