

1/2 HP AC BELT DRIVE WIFI® Garage Door Opener DEPENDABLE PERFORMANCE



KEY FEATURES

- QUIET OPERATION
Belt Drive
- WI-FI
Built In

RELIABLE

1/2 HP AC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

BELT DRIVE SYSTEM FOR QUIET, MAINTENANCE-FREE PERFORMANCE.

WARRANTY 4-YEAR MOTOR, 1-YEAR PARTS.

SMART

BUILT-IN WIFI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

SECURE

SECURITY+ 2.0® SENDS A NEW CODE WITH EVERY REMOTE CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

INCLUDED ACCESSORIES:

Multi-Function Control Panel

Includes lockout controls and accessory programmability.



6080979

882RGDW

3-Button Remote Control

Operates up to 3 openers or MyQ Light Accessories.



2220178

893RGX

POWERFUL ADD-ONS:

Mini Universal Remote Control

Compact and portable to provide quick, easy garage access..



2220185

374UT

Remote Light Control

Plug in any lamp to this device to control it with a smartphone or garage remote.



2220174

825LM

Remote Light Switch

Replaces an existing wall switch to control home lighting with a smartphone or garage remote.



2220183

823LM

MASTERFUL ENGINEERING.

MOTOR

- ½ Horsepower AC
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 6A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Belt Drive Mechanism** (16:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **Solid State Micro-controller** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)



5.75"

15"

10"

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	124"	136"	160"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

7"

Per second for door to move upward

SPEED

7"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

3-Button Remote Control (893 RGX)

Operating Range: ~200'

Operating Temperature: -30°F to 150°F

Frequency:

- Remote Control: 310, 315 and 390 MHz Tri-Band
- Garage Door Opener: Frequency Agile on 310, 315, 390 MHz
- Security+ 2.0 Anti-Burglary Coding

SECURITY +2.0 ENCRYPTED CONTROLS

Multi-Function Control Panel® (882RGDW)

- Program Remote Controls
- Maintenance Alert System
- Easy WiFi Setup

SMART

MyQ® RADIO

902-928 MHz

50-Channel FHSS

(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 1 100-Watt Light Bulb
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

SHIPPING.

SHIPPING WEIGHT (in lbs.)

CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Multi-Function Control Panel (882RGDW)
- 3-Button Remote Control (893RGX)
- Garage Door Opener Head (8155WRGD)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10"4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

20
HEAD

17
RAIL (7')

CONVENIENCE AND SAFETY.

- Alert-2-Close/Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 12 Remote Controls, 1 Keyless Entry System and 16 MyQ Devices



HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation

†: To reduce the risk of injury to persons, only use alert-2-Close/Unattended Close Operation features when installed with a sectional door.