

# Pilot® II with WiFi®

1/2 HP AC CHAIN DRIVE WIFI OPENER WITH INTEGRATED BLUETOOTH TECHNOLOGY



83650RGD - 267

RELIABLE SOLUTION WITH  
POWERFUL PERFORMANCE

## POPULAR FEATURES

**1/2 HP AC MOTOR** is purposefully designed and built to last

**CHAIN DRIVE SYSTEM** for steady performance and industrial strength

**BUILT-IN WIFI** for the easiest way to connect the garage

**MYQ TECHNOLOGY** allows users to know their home is secure

**SECURITY+ 2.0®** safeguards garage access by sending a new code with every click

**POSILOCK®** electronically protects against forced openings

**ALERT-2-CLOSE** signals when a door is being closed by myQ®

**THE PROTECTOR SYSTEM®** invisible light beam auto-reverses the door if there is an obstruction

**REAL-TIME ALERTS** indicate the status of the garage door via email or push notifications

**MONITOR AND CONTROL** the opener from anywhere using mobile devices

**INTEGRATED BLUETOOTH TECHNOLOGY** Reduces setup time and makes it even easier to connect to the myQ app, other myQ devices and smart home technology solutions.

## IN THE BOX



### MULTI-FUNCTION CONTROL PANEL

Operates the garage door opener and lights from inside the garage.

882RGDW • 6081094



### (2) 3-BUTTON REMOTE CONTROLS

Operate up to 3 openers or MyQ light accessories from one remote

893RGX • 2220188



### WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN

877MGX • 2220189

## POWERFUL ADD-ONS



### MYQ SMART CAMERA

Enable secure video capabilities in your garage

SGC1WLM • 6081054



### MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access

374UT • 2220193



### MOTOR

½ horsepower, 1,625 RPM, automatic thermal protection, permanent lubrication

### MECHANICS

- Steel chassis, T-rail and Trolley, full chain drive mechanism (16:1 gear reduction and adjustable door arm)
- Auto-force adjustment for changing weather and environmental conditions
- Electronic limits for easy setup
- AC WiFi logic board with built-in surge suppressor

### POWER

120V AC, 60 Hz voltage, 6.7A current rating, UL listed, 4' power cord (3-prong)

### SPEED

7" per second upward, 7" per second downward

### LIGHTING

Max. 2- 100 watt light bulbs, enhanced CFL (Compact Florescent) compatible, max. 26 watts, solid-state light delay, adjustable time

### DIMENSIONS

Opener Head: 15" L x 10" W x 5.75" H

*Note: when both decorative doors are open, the width of the opener is 30".*

Rail Options:	7'	8'	10'
Installed Length	128"	140"	164"
Max Opening	7'6"	10'	10'

Headroom Clearance Required: 2"



### SECURITY+ 2.0®

Radio Controls:

- Operating range ~200'
- Operating temperature: -35°F to 150°F
- (2) 3-button remote controls and wireless keyless entry with Security+ 2.0 code format
- Garage door opener with Security+ 2.0 code format
- Anti-burglary coding

Encrypted Controls:

- Multi-Function Control Panel®
- Program Remote Controls
- Maintenance Alert System
- Easy WiFi Setup

### MYQ RADIO

- 902-928 MHz 50-channel FHSS (frequently hopping spread spectrum)
- Provides 2-way communication from garage door opener and myQ accessories
- Enables monitoring and control of garage door openers via smartphone or tablet

### HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER)

May require an external adapter depending on the model and year of vehicle. Visit [HomeLink.com](http://HomeLink.com) for additional information



### SHIPPING

#### Carton 1 Shipping Details

Dimensions: 20" x 12" x 10"

Weight: 21 lbs

Contents:

- Garage Door Opener Head
- Multi-Function Control Panel
- (2) 3-Button Remote Control
- Wireless Keyless Entry
- The Protector System® Safety Reversing Sensors

#### Carton 2 Shipping Details

Dimensions: 10'4" x 5" x 5"  
(for 7' Rail)

Weight: 20 lbs

Contents:

- Assembled Solid-Steel Chain T-Rail



### WARRANTIES

Lifetime: Motor

1 Year: Parts

\*: To reduce the risk of injury to persons, only enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.