

Pilot® II with WiFi®

1/2 HP AC CHAIN DRIVE WIFI OPENER WITH INTEGRATED BLUETOOTH TECHNOLOGY



83650RGD - 267

RELIABLE SOLUTION WITH
POWERFUL PERFORMANCE

POPULAR FEATURES

1/2 HP AC MOTOR is purposefully designed and built to last

CHAIN DRIVE SYSTEM for steady performance and industrial strength

BUILT-IN WIFI for the easiest way to connect the garage

MYQ TECHNOLOGY allows users to know their home is secure

SECURITY+ 2.0® safeguards garage access by sending a new code with every click

POSILOCK® electronically protects against forced openings

ALERT-2-CLOSE signals when a door is being closed by myQ®

THE PROTECTOR SYSTEM® invisible light beam auto-reverses the door if there is an obstruction

REAL-TIME ALERTS indicate the status of the garage door via email or push notifications

MONITOR AND CONTROL the opener from anywhere using mobile devices

INTEGRATED BLUETOOTH TECHNOLOGY Reduces setup time and makes it even easier to connect to the myQ app, other myQ devices and smart home technology solutions.

IN THE BOX



MULTI-FUNCTION CONTROL PANEL

Operates the garage door opener and lights from inside the garage.

882RGDW • 6081094



(2) 3-BUTTON REMOTE CONTROLS

Operate up to 3 openers or MyQ light accessories from one remote

893RGX • 2220188



WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN

877MGX • 2220189

POWERFUL ADD-ONS



MYQ SMART CAMERA

Enable secure video capabilities in your garage

SGC1WLM • 6081054



MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access

374UT • 2220193



MOTOR

½ horsepower, 1,625 RPM, automatic thermal protection, permanent lubrication

MECHANICS

- Steel chassis, T-rail and Trolley, full chain drive mechanism (16:1 gear reduction and adjustable door arm)
- Auto-force adjustment for changing weather and environmental conditions
- Electronic limits for easy setup
- AC WiFi logic board with built-in surge suppressor

POWER

120V AC, 60 Hz voltage, 6.7A current rating, UL listed, 4' power cord (3-prong)

SPEED

7" per second upward, 7" per second downward

LIGHTING

Max. 2- 100 watt light bulbs, enhanced CFL (Compact Florescent) compatible, max. 26 watts, solid-state light delay, adjustable time

DIMENSIONS

Opener Head: 15" L x 10" W x 5.75" H

Note: when both decorative doors are open, the width of the opener is 30".

Rail Options:	7'	8'	10'
Installed Length	128"	140"	164"
Max Opening	7'6"	10'	10'

Headroom Clearance Required: 2"



SECURITY+ 2.0®

Radio Controls:

- Operating range ~200'
- Operating temperature: -35°F to 150°F
- (2) 3-button remote controls and wireless keyless entry with Security+ 2.0 code format
- Garage door opener with Security+ 2.0 code format
- Anti-burglary coding

Encrypted Controls:

- Multi-Function Control Panel®
- Program Remote Controls
- Maintenance Alert System
- Easy WiFi Setup

MYQ RADIO

- 902-928 MHz 50-channel FHSS (frequently hopping spread spectrum)
- Provides 2-way communication from garage door opener and myQ accessories
- Enables monitoring and control of garage door openers via smartphone or tablet

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER)

May require an external adapter depending on the model and year of vehicle. Visit HomeLink.com for additional information



SHIPPING

Carton 1 Shipping Details

Dimensions: 20" x 12" x 10"

Weight: 21 lbs

Contents:

- Garage Door Opener Head
- Multi-Function Control Panel
- (2) 3-Button Remote Control
- Wireless Keyless Entry
- The Protector System® Safety Reversing Sensors

Carton 2 Shipping Details

Dimensions: 10'4" x 5" x 5"
(for 7' Rail)

Weight: 20 lbs

Contents:

- Assembled Solid-Steel Chain T-Rail



WARRANTIES

Lifetime: Motor

1 Year: Parts

*: To reduce the risk of injury to persons, only enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.