

DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER

THE SIMPLE BEAUTY OF AN OPEN SPACE.



WARRANTY

- LIFETIME Motor
- 5-YEAR Parts
- 1-YEAR Accessories & Battery Backup

PERFORMANCE

P3
MOTORS®

ULTRA-QUIET ELIMINATES SOUND AND VIBRATION THROUGH THE CEILING BY MOUNTING TO THE WALL.

BATTERY BACKUP POWERS UP EVEN WHEN POWER IS OUT SO YOU CAN GET IN YOUR GARAGE (REQUIRES PURCHASE OF 475LM BATTERY BACKUP).

REMOTE LIGHT DELIVERS 200 WATTS OF LIGHT WITH ADJUSTABLE LIGHT TIME DELAY.

LIFETIME MOTOR AND 5-YEAR PARTS WARRANTY. 1-YEAR BATTERY BACKUP WARRANTY (SOLD SEPARATELY).

CONNECTIVITY



FREE MyQ MOBILE APP ENABLES YOU TO SECURELY MONITOR AND CONTROL YOUR GARAGE DOOR OPENER AND HOUSELIGHTS WITH YOUR SMARTPHONE, TABLET OR COMPUTER.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

SECURE

Security+ 2.0®

SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POWER LOCK DEADBOLT ENSURES THE DOOR CANNOT BE FORCED OPEN.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

TIMER-TO-CLOSE AUTOMATICALLY CLOSE THE DOOR AFTER A PRE-PROGRAMMED NUMBER OF MINUTES .

MOTION DETECTOR PROVIDES RAPID DETECTION AND ILLUMINATION OF GARAGE.

INCLUDED ACCESSORIES:

3-Button Remote Control

Operates up to 3 openers or MyQ Light Accessories.



2220178

893 RGX

MyQ Control Panel

Allows any garage door opener manufactured since 1998 to be controlled by your smartphone, tablet or computer (when paired with the Internet Gateway) - provides the upgrade needed to utilize Security+ 2.0 and MyQ Technology.



6080889

888 RGD

Remote Light

Light your space the way you want to by placing this anywhere in the garage. Uses (2) 100 watt bulbs (not included).



6080434

380 LM

POWERFULL ADD-ONS:

Internet Gateway

Connect your MyQ-Enabled Garage Door Opener and Accessories to the Internet with this device and the free MyQ app.



2220170

828 LM

Remote Light Control

Allows you to control any lamp with your garage door opener remote control or smartphone via the Internet Gateway and the free MyQ app.



2220174

825LM

Door and Gate Monitor

Enables you to monitor and close up to four garage doors or gates from any room in your house.



2220175

829 LM

Battery Backup

Powers up even when power is out so you can get in your garage.



6080435

475LM

MASTERFUL ENGINEERING.

MOTOR

- Heavy-Duty 24V DC
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL* Listed
- 6' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, Plastic Cover**
- **Auto-Force**
- **Electronic Limits**
- **Solid State Microcontroller** with Built-In Surge Suppressor
- **Drive Means** Internal Chain and Sprocket
- **Reduction Means** Gear 63:1



6.85"
7"
16.25"

DIMENSIONS

Max. Door Height: 14ft.
Headroom Clearance Required: 3in. from Center of Torsion Bar

Headroom Clearance Required: 3" from center of Torsion Bar

7.6"
Per second for door to move upward

SPEED
7.6"
Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0*

RADIO CONTROLS

Premium Remote Control
Operating Range: ~200'

Operating Temperature: -40°F to 150°F
Frequency:

- Remote Control: 315 MHz/390 MHz Dual Band*
 - Receiver: Frequency Agile on 310, 315 & 390 MHz
- Security+ 2.0 Anti-Burglary Coding

*Dual Band on Security+2.0 coding only. Premium Remote Control is backwards compatible to all LiftMaster openers manufactured since January 1993.

SECURITY +2.0 ENCRYPTED CONTROLS

MyQ Control Panel*

- Timer-to-Close
- Program Remote Controls, Keypads, MyQ Accessories
- Maintenance Alert System

SMART

MyQ® RADIO

902-928 MHz

50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.*
- Enables remote closing of garage door with key MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.**

*MyQ radio disabled in battery backup mode or when using Alternate Power System (580LM)

**Requires Internet Gateway Accessory Model 828LM

ELECTRICAL

LIGHTING



- Max. 2 100-Watt Light bulbs
- Adjustable Time, Solid State Delay(1.5 to 4.5 minutes)

ENERGY EFFICIENCY

- Approximately 1 Watt Power in Standby mode*
 - Enhanced CFL (Compact Fluorescent) Compatible
- *Occurs at Down Limit When opener's Lights Turn Off

SHIPPING.

SHIPPING WEIGHT (in lbs.)

CARTONS (1)

CARTON 1: 24" x 10" x 12"

- MyQ® Control Panel
- Premium Remote Control
- Garage Door Opener Head
- Power Door Lock
- Cable Tension Monitor
- Remote Light
- The Protector System® Safety Reversing Sensors



CONVENIENCE AND SAFETY.

- The Protector System® Safety Reversing Sensors
- Battery Backup Capable Compatible Model 475LM
- Alert-2-Close/Unattended Close Operation†
- Hands Free Work Lights On
- Emergency/Quick Release
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Door Open/Beam Obstructed / Lights On
- Slow Start Soft Stop



HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation

†: To reduce the risk of injury to persons, only use alert-2-Close/Unattended Close Operation features when installed with a sectional door.