

Quick Specs



TM300/TM320

1.1 MANUFACTURERS

- A. Acceptable Manufacturer: Raynor, which is located at: 1101 East River Rd. P. O. Box 448; Dixon, IL 61021-0448; Toll Free Tel: 800-4-RAYNOR; Tel: 815-288-1431; Fax: 888-598-4790; Email: [request info \(thegarage@raynor.com\)](mailto:request info (thegarage@raynor.com)); Web: <http://www.raynor.com>
- B. ThermaSeal as manufactured by Raynor Garage Doors:
1. Doors:
 - a. Operation:
 - 1) Provide doors designed for manual operation.
 - 2) Provide doors designed for hand chain operation.
 - 3) Provide doors designed for electric motor operation.
 - b. Jamb Construction:
 - 1) Steel jambs with self-tapping fasteners.
 - 2) Wood jambs with lag screw fasteners.
 - 3) Masonry jambs with anchor bolt fasteners.
 - c. Structural Performance Requirements:
 - 1) Wind Loads: Uniform pressure of: _____ psf.
 - d. International Energy Conservation Code (IECC) Requirements:
 - 1) Air Infiltration - Maximum air leakage of 0.4 cfm/ft2 is required.
Testing shall be in accordance with DASMA 105 test procedure.
 2. Sections:
 - a. ThermaSeal TM320:
 - 1) Sections shall be pressure bonded to injected polyurethane foam insulated core. Hinge reinforcement strips shall be 20 gauge galvanized steel, located within section interior. End stiles to be 16 gauge galvanized steel.
 - 2) Material: Steel sandwich construction, 3 inches (76mm) thick, roll formed from commercial quality, hot-dipped galvanized (G40 exterior) steel complying with ASTM A 653. Exterior skin shall be constructed of 20 gauge steel with flush, smooth texture and interior skin shall be 26 gauge steel with embossed stucco texture.
 - 3) Finish: Exterior skin to have two coats of paint, one primer coat and one finish coat.
 - 4) Color: White polyester paint.
 - 5) Insulation: Expanded polyurethane with an R-value of 24.54.
 - b. ThermaSeal TM300:
 - 1) Sections shall be pressure bonded to injected polyurethane foam insulated core. Hinge reinforcement strips shall be 20 gauge galvanized steel, located within section interior. End stiles to be 16 gauge galvanized steel.
 - 2) Material: Steel sandwich construction, 3 inches (76mm) thick, roll

formed from commercial quality, hot-dipped galvanized (G40 exterior) steel complying with ASTM A 653. Exterior skin shall be constructed of 26 gauge steel and interior skin shall be 26 gauge steel with embossed stucco texture.

- 3) Finish: Exterior skin to have two coats of paint, one primer coat and one finish coat.
 - a) Color: White polyester paint.
 - b) Color: PVDF Coated Brown
 - c) Color: PVDF Coated Sepia.
 - d) Color: PVDF Coated Beige.
 - e) Color: PVDF Coated Frost White.
 - f) Color: _____.
 - g) Color: As detailed on the Drawings.
 - h) Color: As determined by Architect from Raynor's ColorWave post paint process featuring 1500 colors of Sherwin Williams Polane Enamel paint.
 - 4) Insulation: Expanded polyurethane with R-value of 24.54.
 - c. Seals: Interior and exterior skins to be separated by continuous hot melt to form thermal break and complete weatherseal along section joint. Bottom of door to have flexible U-shaped vinyl seal retained in aluminum rail. Optional dual-durometer vinyl blade seal on top section to prevent airflow above header
 - d. Trussing: Doors designed to withstand specified windload. Deflection of door in horizontal position to be maximum of 1/120th of door width.
3. Windows: Locations to comply with door elevation drawings.
- b. Window in Rectangular Two-Piece Black Frame:
 - 1) Size: 24 inches by 8 inches (610 mm by 203 mm).
 - a) Glazing: Two panes of 1/8 inch (3.2 mm) thick DSB glass.
 - b) Glazing: Two panes of 1/8 inch (3.2 mm) thick tempered glass.
 - c) Glazing: Two panes of 1/8 inch (3.2 mm) thick DSB glass with breather tube.
 - 2) Size: 24 inches by 12 inches (610 mm by 305 mm).
 - a) Glazing: Two panes of 1/8 inch (3.2 mm) thick DSB glass.
 - b) Glazing: Two panes of 1/8 inch (3.2 mm) thick tempered glass.
 - c) Glazing: Two panes of 1/8 inch (3.2 mm) thick DSB glass with breather tube.
 - 3) Size: 34 inches by 16 inches (864 mm by 406 mm) window in a rectangular two-piece black frame.
 - a) Glazing: Two panes of 1/8 inch (3.2 mm) thick DSB glass
 - c. Full-view window consisting of aluminum stile and rail construction and color matched to door exterior with powdercoat paint. Provide non-impact rated glazing as follows.
 - 1) Glazing: Clear glass. One pane of 1/8 inch (3.2 mm) DSB non-insulated glass.
 - 2) Glazing: Clear glass. One pane of 3/16 inch (4.8 mm) non-insulated glass.
 - 3) Glazing: Clear glass. One pane of 1/4 inch (6.4 mm) non-insulated glass.
 - 4) Glazing: Clear tempered glass. One pane of 1/8 inch (3.2 mm) non-insulated glass.

- 5) Glazing: Clear tempered glass. One pane of 1/4 inch (6.4 mm) non-insulated glass.
- 6) Glazing: Clear tempered glass. One pane of 3/16 inch (4.88 mm) non-insulated glass.
- 7) Glazing: Clear laminated glass. One pane of 1/4 inch (6.4 mm) non-insulated glass.
- 8) Glazing: Clear wire glass. One pane of 1/4 inch (6.4 mm) non-insulated glass.
- 9) Glazing: Tinted bronze glass. One pane of 1/8 inch (3.2 mm) non-insulated glass.
- 10) Glazing: Laminated bronze glass. One pane of 1/4 inch (6.4 mm) non-insulated glass.
- 11) Glazing: Tinted bronze tempered glass. One pane of 1/8 inch (3.2 mm) non-insulated glass.
- 12) Glazing: Tinted smoke grey laminated glass. One pane of 1/4 inch (6.4 mm) non-insulated glass.
- 13) Glazing: 1/2 inch (12.7 mm) insulated clear glass. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.
- 14) Glazing: 1/2 inch (12.7 mm) insulated clear glass with breather tube. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.
- 15) Glazing: 1/2 inch (12.7 mm) insulated clear tempered glass. Two panes of 1/8 inch (3.2 mm) tempered insulated glass.
- 16) Glazing: 1/2 inch (12.7 mm) insulated low E DSB glass. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.
- 17) Glazing: 1/2 inch (12.7 mm) insulated low E tempered glass. Two panes of 1/8 inch (3.2 mm) tempered insulated glass.
- 18) Glazing: 1/2 inch (12.7 mm) insulated Solarban 60 low E tempered glass. Two panes of 1/8 inch (3.2 mm) tempered insulated glass.
- 19) Glazing: Clear acrylic. One pane of 1/8 inch (3.2 mm).
- 20) Glazing: Clear lexan. One pane of 1/8 inch (3.2 mm).
- 21) Glazing: Clear acrylic. One pane of 1/4 inch (6.4 mm).
- 22) Glazing: Clear lexan. One pane of 1/4 inch (6.4 mm).
- 23) Glazing: 1/8 inch (3.2 mm) satin annealed glass.
- 24) Glazing: 1/8 inch (3.2 mm) satin tempered glass.
- 25) Glazing: 1/2 inch (12.69 mm) insulated satin glass. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.
- 26) Glazing: 1/2 inch (12.69 mm) insulated satin tempered glass. Two panes of 1/8 inch (3.2 mm) tempered insulated glass.
- 27) Glazing: 1/4 inch (6.4 mm) laminated white glass.
- 28) Glazing: 1/8 inch (3.2 mm) smoked gray glass.
- 29) Glazing: 1/8 inch (3.2 mm) smoked gray tempered glass.
- 30) Glazing: 1/2 inch (12.69 mm) insulated smoked gray glass. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.
- 31) Glazing: 1/2 inch (12.69 mm) insulated smoked gray glass. Two panes of 1/8 inch (3.2 mm) tempered insulated glass.
- 32) Glazing: 1/8 inch (3.2 mm) lexan smoked gray glazing.
- 33) Glazing: 1/8 inch (3.2 mm) raised pattern obscure glass.
- 34) Glazing: 1/8 inch (3.2 mm) raised pattern obscure tempered glass.
- 35) Glazing: 1/2 inch (12.69 mm) insulated raised pattern obscure glass. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.

- 36) Glazing: 1/2 inch (12.69 mm) insulated raised pattern obscure tempered glass. Two panes of 1/8 inch (3.2 mm) tempered insulated glass.
- 37) Glazing: 1/2 inch (12.69 mm) insulated tinted bronze glass. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.
- 38) Glazing: 1/2 inch (12.69 mm) insulated tinted bronze glass. Two panes of 1/8 inch (3.2 mm) tempered insulated glass.
- 39) Glazing: 1/4 inch (6.4 m) laminated frosted white glass.
- d. Full-view window consisting of aluminum stile and rail construction and color matched to door exterior with powder coat paint. Provide non-impact rated glazing as follows.
 - 1) Glazing: 1 inch (25.4 mm) Insulated Clear Glass. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.
 - 2) Glazing: 1 inch (25.4 mm) Insulated Clear Tempered Glass. Two panes of 1/8 inch (3.2 mm) tempered insulated glass.
 - 3) Glazing: 1 inch (25.4 mm) Insulated Low E DSB Glass. Two panes of 1/8 inch (3.2 mm) DSB insulated glass.
 - 4) Glazing: 1 inch (25.4 mm) Insulated Low E Tempered Glass. Two panes of 1/8 inch (3.2 mm) Tempered insulated glass.
 - 5) Glazing: 1 inch (25.4 mm) Insulated Satin Tempered Glass. Two panes of 1/8 inch (3.2 mm) Tempered insulated glass.
- 4. Mounting: Sections mounted in door opening using:
 - e. Between-Jamb Bracket Mounting: sections mounted between door jambs, seal against exterior perimeter seal installed along vertical and top horizontal edges of jambs.
 - f. Lap Jamb Angle Mounting: section overlap door jambs by 1 inch (25 mm) on each side of door opening.
- 5. Track:
 - a. Material: Hot-dipped galvanized steel (ASTM A 653), fully adjustable for adequate sealing of door to jamb or weatherseal.
 - b. Configuration Type:
 - 1) Configuration Type: Normal Headroom.
 - 2) Configuration Type: Low Headroom.
 - 3) Configuration Type: Vertical Lift.
 - 4) Configuration Type: Lift-Clearance.
 - 5) Configuration Type: Incline.
 - 6) Configuration Type: Contour.
 - c. Track Size:
 - 1) Size: 2 inches (51 mm).
 - 2) Size: 3 inches (76 mm).
 - d. Mounting:
 - 1) Bracket-Mount using adjustable track brackets for use on 2-inch track with wood jambs.
 - 2) Floor-to-Header Angle-Mount consisting of continuous angle extending from the floor up to the door header for use with steel, wood, or masonry jambs. Continuous angle size not less than 2-5/16 inches by 4 inches by 3/32 inch (59 by 102 by 2.5 mm) on 2-inch track and 3-1/2 inches by 5 inches by 3/32 inches (89 by 127 by 2.5 mm) on 3-inch track.
 - 3) Floor-to-Shaft Angle-Mount consisting of continuous angle extending from the floor, past header, completely up to door shaft for use with steel, wood, or masonry jambs. Continuous angle size

- not less than 2-5/16 inches by 4 inches by 3/32 inch (59 by 102 by 2.5 mm) on 2-inch track and 3-1/2 inches by 5 inches by 3/32 inches (89 by 127 by 2.5 mm) on 3-inch track.
- 4) QuikClip: Clip-Angle consisting of clip brackets pre-assembled to continuous angle extending from the floor up to the door header and continuous angle extending from the door header up to the door shaft for use with steel, wood, or masonry jambs. Continuous angle size not less than 2-5/16 inches by 1-1/4 inches by 3/32 inches (59 by 32 by 2.5 mm) on 2-inch track and 3-1/2 inches by 1-1/4 inches by 3/32 inches (89 by 32 by 2.5 mm) on 3-inch track.
- e. Finish:
 - 1) Galvanized.
 - 2) White Powdercoat.
6. Counterbalance:
 - a. Counterbalance System: Provided with aircraft-type, galvanized steel lifting cables with minimum safety factor of 5. Torsion Springs consisting of heavy-duty oil-tempered wire torsion springs on a continuous ball-bearing cross-header shaft.
 - 1) Spring Cycle Requirements: Standard 10,000 cycles.
 - 2) Spring Cycle Requirements: High cycle: _____ cycles.
 7. Hardware:
 - a. Hinges and Brackets: Fabricated from galvanized steel.
 - b. Track Rollers: 2 inches (50.8 mm) diameter consistent with track size, with hardened steel ball bearings.
 - c. Track Rollers: 3 inches (76.2 mm) diameter consistent with track size, with hardened steel ball bearings.
 - d. Perimeter Seal: Provide complete weather stripping system to reduce air infiltration. Weather stripping shall be replaceable.
 - 1) For bracket mounted doors provide climate seal or vinyl seal with aluminum retainer.
 - 2) For angle mounted doors provide angle clip-on seal.
 - e. Furnish door system with locks: Exterior lock with five-pin tumbler cylinder, night latch and steel bar engaging track.
 - f. Furnish door system with locks: Interior lock with dead bolt provided with hole to receive padlock provided by Owner.
 8. ThermaSeal Limited Warranty: Raynor warrants the door sections against defects in material and workmanship, and deterioration due to rust-through for ten years from date of delivery to the original purchaser. Raynor also warrants the door sections against delamination of the insulation from the steel skins for ten years from date of delivery to the original purchaser. Window components are warranted against defects in material and workmanship for one year from date of delivery to the original purchaser. Raynor warrants all hardware and spring components against defects in material and workmanship for one year (or cycle life of the springs) from date of delivery to the original purchaser. Additional Limited Warranty requirements in accordance with manufacturer's full standard limited warranty documentation.